



3006 Oil Petrol

Universele antistatische olieslang		Universeller antistatischer Ölschlauch		Universal antistatic oil hose	
Geschikt voor allround industrieel gebruik, bijv. diesel, paraffine, vet en andere op olie gebaseerde media		Geeignet für den allgemeinen industriellen Einsatz, z. B. Diesel, Paraffin, Fett und andere ölbasierte Medien		Suitable for all-round industrial use, e.g. diesel, paraffin, grease and other oil-based media	
- Binnenwand antistatisch [$R < 10^5 \Omega$] - Buitenwand niet geleidend [$R > 10^8 \Omega$] - Extreem slijtvast - Weer- en ozonbestendig		- Seele antistatisch [$R < 10^5 \Omega$] - Decke nicht leitfähig [$R > 10^8 \Omega$] - Extrem abriebfest - Witterungs- und ozonbeständig		- Tube antistatic [$R < 10^5 \Omega$] - Cover non conductive [$R > 10^8 \Omega$] - Extremely abrasion resistant - Weather and ozone-resistant	
Materiaal binnen:	NBR	Material Seele:	NBR	Material tube:	NBR
Kleur inwendig:	Zwart	Farbe Seele:	Schwarz	Colour tube:	Black
Materiaal buiten:	CR	Material Decke:	CR	Material cover:	CR
Kleur uitwendig:	Zwart	Farbe Decke:	Schwarz	Colour cover:	Black
Inlagen:	Textiel inlagen	Einlagen:	Textileinlagen	Reinforcements:	Textile reinforcements
- Zelfdovende CR buitenwand - Niet geschikt voor aromatische koolwaterstoffen		- Selbstlöschende CR Decke - Nicht geeignet für aromatische Kohlenwasserstoffe		- Self-extinguishing CR rubber cover - Not suitable for aromatic hydrocarbons	

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
7.9	14.3	25	0	221	20
9.5	15.9	60	0	250	20
12.7	17.9	50	0	350	20
15.9	21.5	70	0	417	20

Geleiding | Leitfähigkeit | Conductivity
OHM

Temperatuur | Temperatur | Temperature
Min. -40 °C | Max. 100 °C

Werkdruk | Betriebsdruck | Working pressure
Min. 20 bar | Max. 20 bar

Barstdruk | Platzdruck | Burst pressure
Min. 60 bar | Max. 80 bar

