Rig Supply PW20S

Heavy duty drinkwater bunkerslang zonder spiraal
FDA (CFR 21 §177.2600)

Geschikt voor heavy duty bunkering van zoet water

- Not-toxic FDA conforme binnenwand
- Chemicaliën en weersbestendige buitenwand

Materiaal binnen: NR
Kleur inwendig: Wit
Materiaal buiten: EPDM
Kleur uitwendig: Oranje
Inlagen: Textiel inlagen

- Elektrisch geleidend middels antistatische draad [R < 10^6 Ω/M]

Hochwertiger Trinkwasser Bunkerschlauch ohne Spirale
FDA (CFR 21 §177.2600)

Geeignet zum Bunkern von Frischwasser

- Non-toxic und geruchsneutrale Seele, FDA-konform
- Chemikalien- und witterungsbeständige Decke

Material Seele: NR
Farbe Seele: Weiß
Material Decke: EPDM
Farbe Decke: Orange
Einlagen: Textileinlagen

- Elektrisch leitfähig mittels Kupferlitze [R < 10^6 Ω/M]

Heavy duty potable water bunkering delivery hose
FDA (CFR 21 §177.2600)

Suitable for heavy duty bunkering of fresh water

- Non-toxic and non-tainting FDA compliant tube
- Chemical and weather resistant cover

Material tube: NR
Colour tube: White
Material cover: EPDM
Colour cover: Orange
Reinforcements: Textile reinforcements

- Electrically conductive through antistatic wire [R < 10^6 Ω/M]

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
38.1	52.8	190	0	1400	20
50.8	68.6	254	0	2200	20
76.1	93.6	380	0	3000	20
101.6	120	508	0	4000	20
127	148	635	0	5700	20
152	174.2	760	0	7100	20
203	228.2	1015	0	10500	20

Geleiding | Leitfähigkeit | Conductivity
-M-

Normeringen | Normen | Standards
FDA 177:2600

Temperatuur | Temperatur | Temperature
Min. -30 °C | Max. 80 °C

Werkdruk | Betriebsdruck | Working pressure
Min. 20 bar | Max. 20 bar

Barstdruk | Platzdruck | Burst pressure
Min. 80 bar | Max. 80 bar

Technische wijzigingen voorbehouden, Techn. Änderungen möglich ohne vorige Ankündigung, Tech.data subject to change without prior notice