Airform PLW 20

Rubber perslucht en waterslang

Geschikt voor water, perslucht en algemene industriële toepassigen

- In- en uitwendig glad
- Flexibel en knikvast
- Weerbestendige en slijtvaste buitenwand

Materiaal binnen: SBR
Kleur inwendig: Zwart
Materiaal buiten: SBR
Kleur uitwendig: Zwart
Inlagen: Textiel inlagen

- Geproduceerd in EU

Gummi Pressluft- und Wasserschlauch

Geeignet für Luft, Wasser und allgemeine industrielle Einsatzzwecke

- Innen und außen glatt
- Flexibel - und knickfest
- Abrieb- und witterungsbeständige Decke

Material Seele: SBR
Farbe Seele: Schwarz
Material Decke: SBR
Farbe Decke: Schwarz
Einlagen: Textileinlagen

- Hergestellt in EU

Rubber compressed air and water hose

Suitable for air, water and general industrial applications

- Smooth tube and cover
- Kink resistant and flexible
- Abrasion and weather resistant cover

Material tube: SBR
Colour tube: Black
Material cover: SBR
Colour cover: Black
Reinforcements: Textile reinforcements

- Made in EU

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
6	12	60	0	130	20
8	15	80	0	170	20
10	17	100	0	200	20
13	21	130	0	290	20
16	26	160	0	460	20
19	30	220	0	520	20
25	35	250	0	650	20

Normeringen | Normen | Standards
ISO R 1307

Temperatuur | Temperatur | Temperature
Min. -30 °C | Max. 70 °C

Werkdruk | Betriebsdruck | Working pressure
Min. 20 bar | Max. 20 bar

Barstdruk | Platzdruck | Burst pressure
Min. 60 bar | Max. 60 bar

Technische wijzigingen voorbehouden, Techn. Änderungen möglich ohne vorige Ankündigung, Tech.data subject to change without prior notice