Rig Supply HW

Hoogwaardige bunker zuig- en persslang

Geschikt voor het laden en lossen van tankschepen en als flexibele verbinding tussen verzorgingschip en platform bij offshore installaties

- Geschikt voor koolwaterstoffen tot 55% aromaten, vaste stoffen, modder, bariet, cement en diesel
- 4 koordinlagen met dubbele stalen spiraal
- Zeer slijtvaste en oliebestendige buitenwand

Hochwertiger Bunker Saug- und Druckschlauch

Geeignet für die Be- und Entladung von Tankschiffen und als Versorgungsschlauch auf Offshoreeinrichtungen

- Geeignet für Kohlenwasserstoffe bis zu 55% Aromaten, Feststoffe, Schlamm, Baryt, Zement und Diesel
- 4 Kordeinlagen mit doppelter Federstahlspirale
- Hoch abriebfeste und ölbständige Decke

Premium bunker suction- & discharge hose

Suitable for loading and unloading of tankers and flexible connection between supply vessel and platform in offshore installations

- Suitable for hydrocarbons up to 55% aromatics, solids, mud, barite, cement and diesel
- 4 high tensile cord plies with double steel spiral
- High abrasion and oil resistant cover

Materiaal binnen:	NBR
Kleur inwendig:	Zwart
Materiaal buiten:	NBR/PVC
Kleur uitwendig:	Zwart
Inlagen:	Textiel inlagen + stalen spiraal

Material Seele:	NBR
Farbe Seele:	Schwarz
Material Decke:	NBR/PVC
Farbe Decke:	Schwarz
Einlagen:	Textileinlagen + Stahlspirale

Material tube:	NBR
Colour tube:	Black
Material cover:	NBR/PVC
Colour cover:	Black
Reinforcements:	Textile reinforcements + steel spiral

- Buitenwand vlambestendig volgens U.S. MSHA norm

- Decke flammwidrig konform U.S. MSHA Norm

- Cover flame resistant according U.S. MSHA norm

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
76.2	92.8	456	0.9	3550	20
101.6	119	612	0.9	4950	20
127	148	762	0.9	7440	20
152.4	173	912	0.9	8970	20
203.2	233	1218	0.9	16450	20
254	290	1524	0.9	25670	20

Geleiding | Leitfähigkeit | Conductivity
-M-

Normeringen | Normen | Standards
ISO R 1307

Temperatuur | Temperatur | Temperature
Min. -35 °C | Max. 93 °C

Werkdruk | Betriebsdruck | Working pressure
Min. 20 bar | Max. 20 bar

Barstdruk | Platzdruck | Burst pressure
Min. 60 bar | Max. 60 bar

Technische wijzigingen voorbehouden, Techn. Änderungen möglich ohne vorige Ankündigung, Tech.data subject to change without prior notice